

## Advantages of the cable entry

- Re-closable
- Double-walled insulation
- Airtight and vapour-tight thanks to the "barrier"
- Can be extended under the roof
- Also available with PVC coating
- UV-resistant
- Vermin-free thanks to the "barrier"
- · Very durable and fully recyclable

**Innovative partner** in flue venting & ventilation solutions



**INSULATION** 

Noorderkade 34 1948 NR Beverwijk T: +31 251 22 93 23 E: info@anjo.nl

www.anjo.nl











**NEW** 

## CABLE ENTRY WITH DOUBLE-WALLED INSULATION

## The most complete and innovative cable entry for the roof!

Anjo is expanding its series of cable entries with a double-walled insulated version; the most complete and innovative cable entry for the roof!

The new double-walled, insulated and re-closable cable entry is available in the sizes 60 and 100 mm. This cable entry has an elegant appearance and is easy to open and close. Ideal if cables and/or pipes have to be routed through the roof afterwards.

The supplied adhesive flashing has double-walled insulation, making it resistant to condensation. The additional "barrier" that is supplied ensures an airtight sealing and prevents intrusion by vermin. The adhesive flashing can be connected vapour-tight and airtight and can be extended under the roof. The reclosable hood is made of PP, very strong and UV resistant. The adhesive flashing is provided with a flame-retardant and flame-extinguishing EPS insulation and is also available with a PVC coating.

When developing this product, we paid a lot of attention to circularity and sustainability. The cable entry is made of reusable metals and plastics and can be completely disassembled. All parts are fully recyclable, with little or no loss of quality of the base materials.

	Diameter	Article number
Anjo Cable entry insulated	60mm	42.046.09.06
Anjo Cable entry insulated	100mm	42.046.09.10
Anjo Cable entry insulated with PVC coating	60mm	42.047.09.06
Anjo Cable entry insulated with PVC coating	100mm	42.047.09.10



For more information please go to www.anjo.nl