


## General information

### EasySafe Elbow PP Concentric 60/100 30°



## Specifications

Article number	410470877
Material flue duct	Plastic
Quality class flue duct	PP
Wall thickness flue duct nom (mm)	2,1
Material seal flue duct	EPDM
Material air duct	Plastic
Quality class air duct	PP
Wall Thickness (mm)	1,5
Material seal air duct	TPE
Colour air duct	White (RAL 9016)
Weight (kg)	0,26

## Dimensions

Diameter flue duct nom (mm)	60
Diameter air duct nom (mm)	100
Outer dimensions (l x w x h mm)	155 x 122 x 125

## Application Insights

Intended use	Exhaust of flue gases and supply of combustion air
Location class	For indoor use only

## Technical Specifications

---

Declaration of performance	001-MG-PP DoP
Harmonized standard	EN 14471: 2013 + A1: 2015
System according to DoP	0.9
CE Marking	T120 H1 W2 O00 LI E U1
ζF Flue duct	0,71
ζA Air duct	2
Thermal resistance flue duct (m <sup>2</sup> K/W)	0
Thermal resistance air duct (m <sup>2</sup> K /W)0	
Roughness value flue duct (m)	N.a.
Roughness value air duct (m)	N.a.
Equivalent length (m)	1,4
Other specifications	-


## Mounting and installation

---

Always install according to the national regulations. For safe installation, consult the installation and associated mounting instructions, see [Burgerhout.com](http://Burgerhout.com).

## Graph

Pressure loss versus flow rate



## Table

Flow rate versus pressure loss

Flow rate			Static pressure loss		
[m/s]	[m³/h]	[l/s]	From appliance [Pa]	To appliance [Pa]	Total [Pa]
0	0	0	0,0	0,0	0,0
1	10	3	0,4	0,4	0,8
2	20	6	1,7	1,5	3,2
3	31	8	3,8	3,4	7,3
4	41	11	6,8	6,1	12,9
6	61	17	15,4	13,7	29,1